

Falcon III

Digital Scientific Frame Transfer EMCCD

1024 x 1024 • 10µm x 10µm pixels • Cooled to -70°C • 1MP Scientific •



Key Features and Benefits

NEXT GENERATION photon counting sensitivity

- **Lower read noise of <1e-**
Best sensitivity of any camera technology
- **Faster readout in full resolution**
x 3 times faster than previous generations
- **Higher EM gain of x 5000**
See single photon events
- **Up to 95% QE from back-illuminated sensor**
Optimum Photon collection
- **Strong UV and NIR reponse and ultrawide bandwidth**
From 200nm through to 1100nm
- **Deep cooled to -70°C**
For minimal background events

EMCCD - GEN III
A NEW GENERATION

The Photon Harvester!

Resolution	1024 x 1024
Pixel Size	10µm x 10µm
Readout Noise	<1e-
Frame Rate	34fps
Camera Link	16bit

Specification for Falcon III

Sensor Type	1" Back Thinned Frame Transfer EMCCD
Active Pixel	1024 x 1024
Pixel Size	10µm x 10µm
Active Area	10.2mm x 10.2mm
Full Well Capacity	35ke-
Shift Register Well Depth	200ke-
Non-Linearity	<1%
Readout Noise (RMS)	EM Gain ON: <1 electrons EM Gain OFF: <50 electrons
Full Resolution Frame Rate	34fps
Exposure Time	1ms to >1hr
Dark Current (e/p/s)	0.001 @ -70°C
Digital Output Format	16 bit Camera Link (base configuration)
Peak Quantum Efficiency	95%
Spectral Response	180 - 1100nm
Cooling	-70°C with 10°C coolant
Binning	1x1 up to 32x32
Lens Mount	C-Mount
Synchronisation	Trigger IN and OUT - TTL compatible
Power Supply	12V DC ±0.5V
Total power consumption	<100W
Operating case temperature	-20°C to +55°C
Storage Temperature	-30°C to +60°C
Dimensions (L*W*H) ¹	129mm x 112mm x 94mm
Weight (no lens)	<1.5Kg

Raptor Photonics Limited reserves the right to change this document at any time without notice and disclaims liability for editorial, pictorial or typographical errors.

Ordering Information

Camera

Falcon III EMCCD 1MP digital camera	FA351V-BV-CL
Power Supply Unit	RPL-HR4-K

Optional Accessories

Mini PC with Xcap STD and frame grabber	RPL-PC-EL1
EPIX® EB1 base CL card	RPL-EPIX-EB1
EPIX® XCAP STD software	RPL-XCAP-STD
Camera Link Cable, 2m ²	RPL-MCL-CBL-2M
Thermoelectric Water Chiller Unit	RPL-CHILLER
Chiller Tubing	RPL-WTUBE-NINOX
Optical Lenses ³	RPL-xx-xxxx

Note 1: Dimensions include all connector parts on camera interface


Note 2: Longer CL cable available up to 25M

Note 3: Please consult us to check our range of lenses

Demo is available on request.
Pricing AOR subject to volumes.

Detailed technical drawings
can be downloaded at
www.raptorphotonics.com

Quantum Efficiency



Applications

- Adaptive Optics and Astronomy
- Calcium signaling
- Fluorescence imaging / spectroscopy
- Flow cytometry
- FRET / FRAP / TIRF
- Genome sequencing
- High content screening
- High resolution fluorescence imaging
- Hyperspectral imaging
- Live cell imaging
- Photon counting
- Single molecule detection
- Solar cell inspection
- X-ray & High energy

Document #: INFA351V-BV-CL 319R3