


# Owl 640 II

Low noise, digital VIS-SWIR camera

640 x 512 • 15µm x 15µm Pixel Pitch • Frame rate up to 120 Hz •



## Key Features and Benefits

*The best performing VIS-SWIR camera in the World!*

- **VIS-SWIR technology**  
Compatible with VIS-SWIR illuminators, markers & pointers
- **15µm x 15µm pixel pitch**  
Enables highest resolution VIS-SWIR image
- **Ultra high intrascene dynamic range**  
Enables simultaneous capture of bright & dark portions of a scene
- **On-board Automated Gain Control (AGC)**  
Enables clear video in all light conditions
- **Ultra compact, Low power**  
Ideal for hand-held, mobile or airborne systems

---

Resolution	<b>640 x 512</b>
------------	------------------

---

Frame rate	<b>Up to 120Hz</b>
------------	--------------------

---

Readout noise	<b>36 electrons</b>
---------------	---------------------

---

Wavelength Range	<b>VIS-SWIR</b>
------------------	-----------------

---

## Specification for Owl 640 II

Sensor Type	InGaAs PIN-Photodiode
Active Pixel	640 x 512
Pixel Pitch	15µm x 15µm
Active Area	9.6mm x 7.68mm
Spectral response <sup>1</sup>	0.4µm to 1.7µm
Readout Noise (RMS) <sup>2</sup> LG = Low Gain HG = High Gain	LG: <190e- (174e- typical) HG: <50e- (36e- typical)
Peak Quantum Efficiency	>90% @1.3µm
Full Well Capacity	LG: 650ke- HG: 10ke-
Pixel Operability	>99.5%
Dark Current (e/p/s)	<28,000 @ 15°C
Digital Output Format	14 bit Camera Link (Base Configuration)
Exposure time <sup>3</sup>	10µs to 26.8s
Shutter mode	Global shutter
Frame Rate	Up to 120Hz
Optical Interface	C mount or M42
Dynamic Range	LG: 71dB HG: 49dB
Trigger interface	Trigger IN and OUT - TTL compatible
Power supply	12V DC ±0.5V
TE Cooling	Active
Image Correction	3 point NUC (offset, Gain & Dark Current) + pixel correction
Functions controlled by serial communication	Exposure, intelligent AGC, Non Uniformity Correction, Gamma, Pk/Av, TEC, ALC ROI
Camera Power Consumption <sup>4</sup>	<4W with TEC ON, NUC ON
Operating Case Temperature <sup>5</sup>	-20°C to +55°C
Storage Temperature	-30°C to +60°C
Dimensions (L*W*H) <sup>6</sup>	69.4mm x 50.00mm x 50.00mm
Weight	282g
Raptor Photonics Limited reserves the right to change this document at any time without notice and disclaims liability for editorial, pictorial or typographical errors.	

## Ordering Information

### Camera

Owl 640 II Digital Camera	OW17-VS-CL-640-II
Power Supply Cable	RPL-HR4-K

### Optional Accessories

Mini PC with XCAP Std and frame grabber	RPL-PC-EL1
EPIX® EB1 Frame Grabber	RPL-EPIX-EB1
EPIX® XCAP Std software	RPL-XCAP-STD
Camera Link Cable (2m) <sup>7</sup>	RPL-MCL-CBL-2M
Optical Lenses <sup>8</sup>	RPL-xx-xxxx

Note 1: Optional filters available: Low, High or bandpass.

Note 2: Typical readout noise is calculated from an average of the last 20 cameras shipped.

Note 3: In practice, the maximum exposure time will be dark current limited.

Note 4: Measured in an ambient of 25°C with adequate heat sinking. For more detailed power consumption values, please refer to the user manual.

Note 5: Extended operating temperature range on request.

Note 6: Dimensions include all connector parts on the camera interface.


Note 7: Longer Camera Link cable available.

Note 8: Please consult us to check our range of lenses.

Demo is available on request.  
Pricing AOR subject to volumes.

Detailed technical drawings  
can be downloaded at  
[www.raptorphotonics.com](http://www.raptorphotonics.com)

## Quantum Efficiency



\*Data supplied by sensor manufacturer

## Applications

### Surveillance

- 860, 1064 & 1550nm laser line detection
- Active Imaging
- Airborne Payload
- Hand Held Systems
- Imaging through Fog
- Range Finding
- Vision enhancement

### Scientific

- Astronomy
- Beam Profiling
- Hyperspectral Imaging
- Semiconductor Inspection
- Solar Cell Inspection
- Thermography

Document #: INOWL17-VS-CL-640-II 0120



Willowbank Business Park  
Larne, Co Antrim  
BT40 2SF,  
Northern Ireland

Raptor Photonics Ltd. (UK)  
T: +44(0)2828 270 141  
E: sales@raptorphotonics.com  
[www.raptorphotonics.com](http://www.raptorphotonics.com)

Raptor Photonics Inc. (USA)  
T: +1 (877) 230-4836  
E: sales@raptorphotonics.com  
[www.raptorphotonics.com](http://www.raptorphotonics.com)

